



pro series

Security Cable


Garland's Pro Series range is the experts' choice for high quality cables.

# Part No: MC146BN

Description	Stranded 21AWG (14/0.2mm) PACW, 6Cores, PVC Insulation, PVC Sheath.
Applicable Standards	AS/CA S-008, BS4737-3.30, AS 1049
Suitable Applications	For inter-connecting wiring, suitable for use in Security/Intruded Alarm system; Use in low voltage/low current applications such as intercommunication.
	Not suitable for mains connection.

### **Cable Construction Drawing**

#### **Cable Construction Relative Parts**





## Cable Description

Conductor	AWG	Stranding	Area(mm <sup>2</sup> )	Diameter(mm)	Material	
	21	14/0.2	0.44	0.87	PACW	
Insulation	Cores :6Material :PVCColour :White, Blue, Red, Black, Yellow, GreenNominal Thickness (mm) :0.3Nominal OD (mm) :1.5			Green		
Sheath		: Thickness (mn OD (mm) :		Terra Brown(RAL 8028) : 0.65		



With Garland, you are always well connected.



Industrial / Power / Data / Security / Fibre

pro series

## Garland's Pro Series range is the

experts' choice for high quality cables.

Electrical Properties			
Voltage Rating	ELV		
Max. Conductor DC Resistance @ 20°C	<b>45.2</b> Ω/km		
Min. Insulation Resistance @ 20°C	50MΩ.km		
Voltage Test: Conductor to core	1.5 kV ac/1min		
Voltage Test: Core to sheath	3.0 kV ac/1min		
Mechanical Properties			
Operating Temperature Range	-15 to 70°C		
Max. Recommended Pulling Tension	166N		
Min. Bend Radius (install)	61mm		
Approximate Mass	5.47kg/100m		
Sheath Printing	GARLAND SECURITY CABLE MC146 - 6 x 14/0.2 22AWG - MM/YYYY - "Mmark"		

# Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
100m	Plastic Reel	10 x 4.5 x 4.5"	4R	

Document Change Record	Issue	Date	Prepared by	Approved By
	01	23-11-2012	LLS	Pent
Change History	Issue	Change		



With Garland, you are always well connected.