



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MC147S

Description	Stranded 21AWG PACW, 7Cores, PVC Insulation, Aluminium Polyester
Description	Tape Overall Screen, Stranded 24AWG TACW Drain Wire, PVC Sheath.

AS/ACIF S008, BS4737-3.30 Applicable Standards

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description					
Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	21	14/0.2	0.44	0.87	PACW
Insulation	Cores: 7 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green, Brown Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5				
Screen	Material : Al. Polyester Tape			Coverage: 100%	
Drain Wire	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
Dialii Wile	24	7/0.2	0.22	0.6	PACW

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Sheath Material: PVC
Colour: Grey
Nominal Thickness (mm): 0.7
Nominal OD (mm): 6.6

Electrical Properties					
Voltage Rating	ELV				
Max. Conductor DC Resistance @ 20°C	45.2Ω/km				
Min. Insulation Resistance @ 20°C	50MΩ.km				
Voltage Test: Conductor to core	1.5 kV ac/1min				
Voltage Test: Core to sheath	3.0 kV ac/1min				

Mechanical Properties	
Operating Temperature Range	-15 to 70°C
Max. Recommended Pulling Tension	215N
Min. Bend Radius (install)	65.5mm
Approximate Mass	7.0kg/100m
Sheath Printing	GARLAND SECURITY CABLE MC147S - 7 X 14/0.20 22AWG OAS - MM/YYYY - "Mmark"

Supply Information					
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet	
100m	Plastic Reel	10 x 4.5 x 5"	2R		
500m	Wooden Reel	W39 x 21.8cm	1R		

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances