



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: MCP1SJFP

Stranded 24AWG TACW, Single Twisted Pair, PP Insulated, Jelly Filled, Description Cotton Paper, Aluminium Polyester Tape Overall Screen, TACW 24AWG

Drain Wire, PE Sheath.

Applicable Standards AS/ACIF S008, UL758, EIA-RS422

Used as signal transmission and connection of checking appliances of

distribution system, computer system


Designed for outdoor use including underground applications. Suitable Applications

Suitable for direct burial.

Cable Construction Drawing

Cable Construction Relative Parts









Cable Description					
Conductor	AWG	Standing	Area(mm ²)	Diameter(mm)	Material
	24	7/0.2	0.22	0.6	TACW
Insulation		: Thickness (mr OD (mm) :	1 PP Blue/White n): 0.3 1.2		
Filler	Material	: Jelly Filled			
	Material	: Cotton Paper		Coverage: 100%	

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the

experts' choice for high quality cables.

Screen	Material: Al. Polyester Tape			Coverage: 100%	
Drain Wire	AWG	Standing	Area(mm ²)	Diameter(mm)	Material
	24	7/0.2	0.22	0.6	TACW
Sheath	Material: PE Colour: Black Nominal Thickness (mm): 0.75 Nominal OD (mm): 4.4				

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	95.3Ω/km
Min Insulation Resistance @ 20°C	10 000MO km

Mechanical Properties	
Operating Temperature Range	-30 to 70℃
Max. Recommended Pulling Tension	30N
Min. Bend Radius (install)	44mm
Approximate Mass	2.04kg/100m

Supply Information					
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet	
100m	Plastic Reel	10 x 4.5 x 2.5"	10R		
500m	Wooden Reel	W30 x H21.8cm	1R		

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances

