



Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Part No: TCW14GY

Stranded 21AWG (14/0.2mm) PACW, Figure 8 construction, PVC Description

Insulation.

Applicable Standards AS/CA S-008


For the wiring of electronic and allied equipment, extension speakers, **Suitable Applications**

security system etc.

Cable Construction Drawing

Cable Construction Relative Parts











Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material	
	24	14/0.2	0.215	0.6	PACW	
Insulation	l .	: Thickness (mn OD (mm) :	Grey/Black S			

Electrical Properties	
Voltage Rating	ELV
Max. Conductor DC Resistance @ 20°C	45.2Ω/km
Min. Insulation Resistance @ 20°C	50MΩ.km

With Garland, you are always well connected.







Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the

experts' choice for high quality cables.

Voltage Test: Conductor to core	1.5 kV ac/1min		
Mechanical Properties			
Operating Temperature Range	-15 to 70℃		
Max. Recommended Pulling Tension	61N		
Min. Bend Radius (install)	22mm		
Approximate Mass	1.75kg/100m		
Sheath Printing	GARLAND FIGURE 8 TCW14 - 2 X 14/0.2		

Supply Information						
Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet		
100m	Plastic Reel	7 x 4.5 x 3.5"	20R			

Document Change Record	Issue	Date	Prepared by	Approved By
	01	05-12-2012	LLS	Pent
Change History	Issue	Change		

