Security Cable





Part No: MC144-W

Description Stranded 21AWG PACW, 4 Cores, PVC Insulation, PVC Sheath.

Applicable Standards AS/CA S-008, BS4737-3.30, AS 1049

Suitable Applications For inter-connecting wiring, suitable for use in Security/Intruded


Alarm system; Use in low voltage/low current applications such as

intercommunication.

Not suitable for mains connection.

nages





See supply information table for full details of jacket colour options.

Image for illustration purposes only.





Conductor	Material	PACW	
	No. of Strands	14	
	Strand Size	0.2 mm	
Insulation	Cores	4	
	Material	V-75 PVC	
	Colour	White, Blue, Red, Black	
	Nominal Thickness (mm)	0.35	
	Nominal Diameter (mm)	1.5	
Sheath	Material	V-75 PVC	
	Colour	Refer to Packing Table	
	Diameter (mm)	4.7	
	Average Thickness (mm)	0.5	
	Insulation	No. of Strands Strand Size Insulation Cores Material Colour Nominal Thickness (mm) Nominal Diameter (mm) Sheath Material Colour Diameter (mm)	



Security Cable



Properties	Voltage Rating	ELV
	Operating Temperature Range	-15 to 7°C
	Max. Recommended Pulling Tension	120N
	Min. Bend Radius (install)	50 mm
	Approximate Mass	3.4kg/100 m

Supply Information	Part Number	Pack Size	Jacket Colour	Qty Per Carton/Reel	Cartons Per Pallet
	MC144WH100W	100m	White	6Reels	32 x 6 or 24 x 6
	MC144WH300BW	300m	White	-	45

- Madison reserves the right to make changes to the products described in this specification without prior notice
- All values subject to factory tolerances